

**Steven M. Hoffberg**

---

**From:** Steven M. Hoffberg [steve@hoffberg.org]  
**Sent:** Thursday, November 18, 2004 12:18 PM  
**To:** 'Nguyen, Nga'  
**Subject:** 09/599,163 tvs\_client.c

```
/* -----
 * -----
 * tvs_client - implements the client interface to TVS
 * Copyright (c) 1995 Newshare Corporation
 * -----
 */
```

```
#include <stdio.h>
#include <unistd.h>
#include <stdlib.h>
#include <string.h>
#include <bstring.h>
#include <time.h>
#include <ctype.h>
#include <signal.h>
#include <sys/un.h>
#include <sys/errno.h>
#include <sys/types.h>
#include <sys/uio.h>
#include <sys/time.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <netinet/tcp.h>
#include <netdb.h>
#ifdef SOLARIS2
#include <arpa/inet.h>
#endif /* SOLARIS2 */
#ifdef IRIX
#include <unistd.h>
#endif /* IRIX */
```

```
#include "tvs.h"
#include "tvs_client.h"
#include "tvs_config.h"
#include "tvs_log.h"
#include "tvs_error.h"
#include "tvs_profile.h"
#include "tvs_util.h"
```

```
#define TVSC_MAX_TOKEN_LENGTH 72
#define TVSC_MAX_BUFLen TVSC_MAX_TOKEN_LENGTH*2
```

```

#define TVS_MAX_CONNECT_RETRIES 4

#define FREE(x) free(x)          /* so I can use my own for debug */
#define MALLOC(x) malloc(x)

PRIVATE int tvs_is_initialized = 0;
PRIVATE int service_initialized = 0;

/* address structures for myself, and my TVS server (once obtained) */

PRIVATE struct sockaddr_in client_sa, server_sa;
PRIVATE int client_sock, clien, serlen;

/*
 * server identification information
 * (I get this from tvs_request_service(), and also put it into a disk file)
 */

PRIVATE unsigned short tvs_server_id = 0;
PRIVATE char          *tvs_server_name = (char *) NULL;
PUBLIC TVS_SERVER     tvss_sid = (TVS_SERVER) NULL;

/* everybody's message buffer for stuff returned from TVS */

PRIVATE char response[TVSC_MAX_BUFLen];
PRIVATE int  resplen = TVSC_MAX_BUFLen;

#if 0
/* -----
 * wrappers
 * -----
 */

PRIVATE void
tvs_free(void *mem)
{
    free(mem);
}

PRIVATE void *
tvs_malloc(int mem)
{
    return (void *) malloc(mem);
}
#endif

/* -----
 * close up shop
 * -----
 */

```

```

PRIVATE int
teardown_service()
{
    close(client_sock);
    client_sock = 0;
    service_initialized = 0;
    return 1;
}

/* -----
 * initialize some globally useful structures
 * -----
 */

PRIVATE int
init_service()
{
    struct servent *sp;

    bzero(&client_sa, sizeof(struct sockaddr_in));

    /* build and bind my client side */

    client_sa.sin_family = AF_INET;
    client_sa.sin_port = htons(0);
    client_sa.sin_addr.s_addr = htonl(INADDR_ANY);

    clilen = sizeof(struct sockaddr_in);

    client_sock = socket(AF_INET, SOCK_DGRAM, 0);
    if (!client_sock) return 0;

    if (bind(client_sock, (struct sockaddr *) &client_sa, clilen) < 0)
        return 0;

    /* set up server boilerplate */

    bzero(&server_sa, sizeof(struct sockaddr_in));
    serlen = sizeof(struct sockaddr_in);

    /*
    sp = getservbyname(SERVICE_NAME, "udp");
    if (!sp) return 0;
    */

    sp = (struct servent *) MALLOC(sizeof(struct servent));

    sp->s_port = htons(CLICKSHARE_PORT);

    server_sa.sin_port = sp->s_port;
    server_sa.sin_family = AF_INET;

```

```

    FREE(sp);

    service_initialized |= 1;
    return 1;
}

/* -----
 * handle this boring name/addr lookup stuff.
 * -----
 */

PRIVATE int
build_server_addr(char *server)
{
    struct hostent *hp;

    hp = gethostbyname(server);
    if (hp == (struct hostent *) NULL) {
        sprintf(msgString, "tvsc_request_service: can find server host [%s]\n",
            server);
        LogMsg(LOG_INFO, msgString);
        return 0;
    }

    bcopy(hp->h_addr_list[0], &(server_sa.sin_addr.s_addr), hp->h_length);
#ifdef DEBUG
    printf("using server addr: %s\n", inet_ntoa(server_sa.sin_addr));
#endif
    return 1;
}

/* -----
 * response packets from TVS contain an ACK as the first character of the
 * packet. This ACK is the encode_command() form of enum request_type if
 * the command was successful, OR the same logically ORed with TVS_NAK if not.
 * If not successful, the remainder of the packet is an error code in
 * character form (as found in tvs_error.h).
 * -----
 */

PRIVATE int
tvsc_success(char cmd, char response)
{
    /* response contains NAK */

#ifdef DEBUG
    fprintf(stderr, "cmd: %c response: %c (0x%x)\n", cmd, response,
        (response & TVS_NAK));
#endif /* DEBUG */
    if ((cmd & TVS_NAK)) return 0;
}

```

```

/* make sure that the response actually contains the command */

if (cmd != response) return 0;

return 1;
}

/* -----
 * -----
 * here's the main functionality
 * -----
 */

/* -----
 * PACKET FORMAT
 * cmd 1 char
 * host IP 4 bytes
 * PM id 4 chars
 * -----
 */

PRIVATE int
tvsc_request_service()
{
    extern int tvs_server_error;

    char cmd;
    char **servers;          /* will be NULL terminated list of hostnames */
    struct iovec iobuf[3];
    unsigned long haddr;

    int got_response = 0;
    unsigned long id_pm;

    /* set up net, and a list of servers to try */

    if (!service_initialized)
        (void) init_service();

    servers = tvs_servers;
    if (!servers) return 0;

    tvs_server_error = TVS_NO_SERVER_ERROR;

    /* create my packet */

    cmd = encode_command(TVS_REQUEST_SERVICE);
    iobuf[0].iov_base = (caddr_t) &cmd;          /* command */
    iobuf[0].iov_len = 1;

```

```

/* my own address */

if (!get_my_address(&haddr)) {
    LogMsg(LOG_ERR, "server unable to get own host address.");
    return 0;
}

iobuf[1].iov_base = (caddr_t) &haddr;
iobuf[1].iov_len = sizeof(unsigned long);

/* my PM id */

id_pm = htonl(tvs_pm_id);
iobuf[2].iov_base = (caddr_t) &id_pm;
iobuf[2].iov_len = sizeof(unsigned long);

/* try each of our servers till we get a token or die */

while(*servers) {
    if(!build_server_addr(*servers)) {
        servers++;
        continue;
    }
#ifdef DEBUG
    fprintf(stderr, "request service: trying: %s\n", *servers);
#endif /* DEBUG */
    if (connect(client_sock, (struct sockaddr *) &server_sa, serlen) < 0) {
        perror("connect");
        servers++;
        continue;
    }

    resplen = TVSC_MAX_BUFLen;
    if (rdp_vtransact(client_sock, &iobuf[0], 3, response, &resplen) > 0) {
#ifdef DEBUG
        fprintf(stderr, "got response: %c: ", response[0]);
        if (isalpha(response[1]))
            fprintf(stderr, "%s\n", &response[1]);
        else
            fprintf(stderr, "0x%x 0x%x 0x%x 0x%x 0x%x 0x%x\n",
                response[1], response[2], response[3], response[4],
                response[5], response[6]);
#endif /* DEBUG */
        response[resplen] = '\0';
        got_response++;
        break;
    }
    else
        servers++;
}

```

```

if (!got_response)
    return 0;

if (!tvsc_success(cmd, response[0])) {
    tvs_set_return_string(&response[1]);
    return 0;
}

/*
 * store up information about the server we've connected to
 * NOTE: I will need this later if I have to restart
 * NOTE: address stays in net byte order, id converts to host.
 */

memcpy(&tvss_server_id, &response[5], sizeof(unsigned short));

tvss_server_name = (char *) MALLOC(strlen(*servers)+1);
strcpy(tvss_server_name, *servers);
tvss_sid = tvs_new_server_id(server_sa.sin_addr.s_addr,
                             ntohs(tvss_server_id));

/* save this connection name for next time */
tvss_save_server_name(tvss_sid);

sprintf(msgString, "obtained %s for Clickshare service", tvss_server_name);
LogMsg(LOG_NOTICE, msgString);
return 1;
}

/* -----
 * PACKET FORMAT
 * cmd 1 char
 * host IP 4 bytes
 * PM id 4 chars
 * -----
 */

PRIVATE int
tvsc_drop_service()
{
    char cmd;
    struct iovec iobuf[3];
    unsigned long haddr;
    unsigned long id_pm;

    cmd = encode_command(TVS_DROP_SERVICE);
    iobuf[0].iov_base = (caddr_t) &cmd;          /* command */
    iobuf[0].iov_len = 1;

    if (!get_my_address(&haddr)) {

```

```

    LogMsg(LOG_ERR, "server unable to get own host address.");
    exit(1);
}

iobuf[1].iov_base = (caddr_t) &haddr;
iobuf[1].iov_len = sizeof(unsigned long);

id_pm = htonl(tvs_pm_id);
iobuf[2].iov_base = (caddr_t) &id_pm;
iobuf[2].iov_len = sizeof(unsigned long);

resplen = TVSC_MAX_BUFLen;
rdp_vtransact(client_sock, &iobuf[0], 3, response, &resplen);
response[resplen] = '\0';
tvs_set_return_string(&response[1]);
if (!tvs_success(cmd, response[0])) {
    sprintf(msgString, "drop error: %s (%d)\n", &response[1], resplen);

    /* it is not always fatal if the drop_service() fails, so just notify */

    LogMsg(LOG_NOTICE, msgString);
    return 0;
}

/* clear out current service IDs */

tvs_server_id = 0;
tvs_server_name = (char *) NULL;

/* release everything */

teardown_service(); /* so I can "clean start" */
tvs_unlink_server_name_file();
return 1;
}

/* -----
 * This is called first (upon startup) to assure that we start a clean
 * session with TVS. This takes care of problems when/if previous server
 * invocations die abnormally.
 * -----
 */

PRIVATE int
tvsc_invalidate_service()
{
    char *server_host;
    int tvss_id;
    unsigned long ss_addr;

```



```

server_host = tvs_load_server_name (&tvss_id);
if (!server_host)
    return 1;

/* if I have successfully read contents, assume I had better contact
 * the old server to drop my old "connection".
 */

init_service();

if (!strcmp(server_host, "0x", 2)) {
    sscanf(server_host, "0x%lx", &ss_addr);
    bcopy((char *) &ss_addr, &(server_sa.sin_addr.s_addr),
        sizeof(unsigned long));
}
else
    build_server_addr(server_host);

if (connect(client_sock, (struct sockaddr *) &server_sa, serlen) < 0)
    return -1;

/* let drop service handle all this */

tvsc_drop_service();
return 1;
}

/* -----
 * PACKET FORMAT
 * cmd 1 char
 * user's host IP 4 bytes (in the profile)
 * user's profile (encoded) variable bytes
 * -----
 */

PRIVATE TVS_TOKEN
tvsc_request_token(TVS_PROFILE prof)
{
    char *request;
    char cmd;
    struct iovec iobuf[2];
    TVS_TOKEN token;

    if (!tvs_is_initialized)
        return 0;

    cmd = encode_command(TVS_NEW_TOKEN);
    iobuf[0].iov_base = (caddr_t) &cmd;          /* command */
    iobuf[0].iov_len = 1;

    request = tvs_encode_profile(prof); /* encode the profile we're sending */

```

```

if (!request) return 0;

iobuf[1].iov_base = (caddr_t) request;
iobuf[1].iov_len = strlen(request);

resplen = TVSC_MAX_BUFLen;
rdp_vtransact(client_sock, &iobuf[0], 2, response, &resplen);
response[resplen] = '\0';
tvs_set_return_string(&response[1]);
if (tvsc_success(cmd, response[0])) {
    token = (char *) MALLOC(strlen(response));
    strcpy(token, &response[1]);
}
else {
    sprintf(msgString, "request token error: %s (%d)\n",
            &response[1], resplen);
    LogMsg(LOG_ERR, msgString);
    token = (TVS_TOKEN) NULL;
}

FREE(request);
return token;
}

/* -----
 * PACKET FORMAT
 * cmd 1 char
 * user's host ip addr (incoming connection) 4 bytes
 * user's token (variable bytes)
 * -----
 */

PRIVATE TVS_PROFILE
tvsc_request_validation(TVS_TOKEN token, unsigned long host_id)
{
    char cmd;
    struct iovec iobuf[3];
    TVS_PROFILE prof;

    if (!tvs_is_initialized)
        return 0;

    cmd = encode_command(TVS_VALIDATE_TOKEN);
    iobuf[0].iov_base = (caddr_t) &cmd;          /* command */
    iobuf[0].iov_len = 1;

    iobuf[1].iov_base = (caddr_t) &host_id;
    iobuf[1].iov_len = sizeof(unsigned long);

    iobuf[2].iov_base = (caddr_t) token;
    iobuf[2].iov_len = strlen(token);

```

```

resplen = TVSC_MAX_BUFLen;
rdp_vtransact(client_sock, &iobuf[0], 3, response, &resplen);
response[resplen] = '\0';
tvs_set_return_string(&response[1]);
if (tvsc_success(cmd, response[0])) {
    prof = tvs_decode_profile(&response[1]);
}
else {
    /* server return message will probably contain address to forward to */
    sprintf(msgString, "error validating token: %s\n",
            tvs_get_server_return());
    LogMsg(LOG_NOTICE, msgString);

    prof = (TVS_PROFILE) NULL;
}

return prof;
}

/* -----
 * PACKET FORMAT
 * cmd 1 char
 * user's token (variable bytes)
 * reason 4 bytes
 * -----
 */

PRIVATE int
tvsc_request_invalidate(TVS_TOKEN token, int reason)
{
    char cmd;
    struct iovec iobuf[2];

    if (!tvs_is_initialized)
        return 0;

    cmd = encode_command(TVS_INVALIDATE_TOKEN);
    iobuf[0].iov_base = (caddr_t) &cmd;          /* command */
    iobuf[0].iov_len = 1;

    iobuf[1].iov_base = (caddr_t) token;
    iobuf[1].iov_len = strlen(token);

    /* reason not currently used */

    /* iobuf[2].iov_base = (caddr_t) &reason;
    * iobuf[2].iov_len = sizeof(int);
    */

    resplen = TVSC_MAX_BUFLen;

```

```

rdp_vtransact(client_sock, &iobuf[0], 2, response, &resplen);
response[resplen] = '\0';
tvs_set_return_string(&response[1]);
if (tvsc_success(cmd, response[0])) {
    return 1;
}
else {
    sprintf(msgString, "error invalidating token: %s (%d)\n",
            &response[1], resplen);
    LogMsg(LOG_NOTICE, msgString);
}

return 0;
}

/* -----
 * PACKET FORMAT
 * cmd 1 char
 * server id (variable bytes)
 * -----
 */

PRIVATE char *
tvsc_request_id(TVS_SERVER tvs_id)
{
    char cmd;
    struct iovec iobuf[2];
    unsigned short nid;
    char *resp = (char *) NULL;

    if (!tvs_is_initialized)
        return 0;

    cmd = encode_command(TVS_IDENTIFY_SERVICE);
    iobuf[0].iov_base = (caddr_t) &cmd;
    iobuf[0].iov_len = 1;

    nid = tvs_get_server_id(tvs_id);
    nid = htons(nid);
    iobuf[1].iov_base = (caddr_t) &nid;
    iobuf[1].iov_len = sizeof(unsigned short);

    resplen = TVSC_MAX_BUFLen;
    rdp_vtransact(client_sock, &iobuf[0], 2, response, &resplen);
    response[resplen] = '\0';
    tvs_set_return_string(&response[1]);
    if (tvsc_success(cmd, response[0])) {
        resp = (char *) MALLOC(resplen);
        strcpy(resp, &response[1]);
    }
    else {

```

```

    sprintf(msgString, "error getting TVS server ID: %s (%d)\n",
            &response[1], resplen);
    LogMsg(LOG_NOTICE, msgString);
}

return resp;
}

/* -----
 * -----
 * Public interface to the TVS server
 * (These are really just error wrappers around the "raw" client functions).
 * -----
 * -----
 */

/* -----
 * tvs_initialize_service - start a session with TVS
 * -----
 */

PUBLIC TVS_SERVER
tvs_initialize_service(char *tvs_conf)
{
    extern int tvs_error;

    tvs_error = TVS_NO_ERROR;

    /* locate all my configuration files */

    if (!tvs_read_config(tvs_conf)) {
        LogMsg(LOG_ERR, "problem reading server configuration file:");
        LogMsg(LOG_ERR, tvs_error_msg);
        return (TVS_SERVER) NULL;
    }

    /* try to patch things up if a previous session with TVS crashed */

    tvsc_invalidate_service();

    /* now, request a "fresh service" */

    if (tvsc_request_service())
        tvs_is_initialized |= 1;
    else {
        tvs_error = TVS_SERVER_ERROR;
        tvs_is_initialized = 0;
    }

    return tvss_sid;
}

```

```

/* -----
 * tvs_new_token - ask the TVS server for a new TVS token for a given user.
 * -----
 */

```

```

PUBLIC TVS_TOKEN
tvs_new_token(TVS_PROFILE prof)
{
    extern int tvs_error;
    TVS_TOKEN token;

    tvs_error = TVS_NO_ERROR;

    if (!prof) {
        tvs_error = TVS_PROFILE_NOT_PROVIDED;
        return (TVS_TOKEN) NULL;
    }

    if (!tvs_is_initialized) {
        tvs_error = TVS_SERVER_NOT_INITIALIZED;
        return (TVS_TOKEN) NULL;
    }

    if ((token = tvsc_request_token(prof)) == (TVS_TOKEN) NULL) {
        tvs_error = TVS_SERVER_ERROR;
        return (TVS_TOKEN) NULL;
    }

    return token;
}

```

```

/* -----
 * tvs_validate_token - ask TVS if a given token is valid
 * -----
 */

```

```

PUBLIC TVS_PROFILE
tvs_validate_token(TVS_TOKEN token, unsigned long h_id)
{
    extern int tvs_error;
    TVS_PROFILE prof;

    tvs_error = TVS_NO_ERROR;

    if (!token) {
        tvs_error = TVS_INVALID_TOKEN_PROVIDED;
        return (TVS_PROFILE) NULL;
    }

    if (!tvs_is_initialized) {

```

```

    tvs_error = TVS_SERVER_NOT_INITIALIZED;
    return (TVS_PROFILE) NULL;
}

if ((prof = tvsc_request_validation(token, h_id)) == (TVS_PROFILE) NULL) {
    tvs_error = TVS_SERVER_ERROR;
    return (TVS_PROFILE) NULL;
}

return prof;
}

/* -----
 * tvs_invalidate_token - ask TVS to trash a given token
 * -----
 */

PUBLIC int
tvs_invalidate_token(TVS_TOKEN token, int reason)
{
    extern int tvs_error;
    tvs_error = TVS_NO_ERROR;

    if (!token) {
        tvs_error = TVS_INVALID_TOKEN_PROVIDED;
        return 0;
    }

    if (!tvs_is_initialized) {
        tvs_error = TVS_SERVER_NOT_INITIALIZED;
        return 0;
    }

    if (!tvsc_request_invalidate(token, reason)) {
        tvs_error = TVS_SERVER_ERROR;
        return 0;
    }
    return 1;
}

/* -----
 * tvs_identify_tvs_server - get the id string of a given TVS server
 * -----
 */

PUBLIC char *
tvs_identify_tvs_server()
{
    char *id;
    extern int tvs_error;

```

```

    tvs_error = TVS_NO_ERROR;

    if (!tvss_sid) {
        tvs_error = TVS_NO_SERVER_ID_GIVEN;
        return (char *) NULL;
    }

    if (!tvs_is_initialized) {
        tvs_error = TVS_SERVER_NOT_INITIALIZED;
        return (char *) NULL;
    }

    id = tvsc_request_id(tvss_sid);
    if (!id)
        tvs_error = TVS_SERVER_ERROR;

    return id;
}

/* -----
 * tvs_drop_service - cleanly disconnect from the TVS server
 * -----
 */

PUBLIC void
tvs_drop_service()
{
    extern int tvs_error;

    tvs_error = TVS_NO_ERROR;
    tvsc_drop_service();
    return;
}

/* -----
 * tvs_invalidate_service - clean-up after a bad disconnect from the TVS
 * server (OK, to call this under ANY circumstance at startup -- before
 * tvs_initialize_server).
 * -----
 */

PUBLIC void
tvs_invalidate_service()
{
    extern int tvs_error;
    tvs_error = TVS_NO_ERROR;

    tvsc_invalidate_service();
    return;
}

```



```
/* -----  
 * tvs_destroy_token - get rid of this token  
 * -----  
 */
```

```
PUBLIC void  
tvs_destroy_token(TVS_TOKEN token)  
{  
    FREE(token);  
}
```

Very truly yours,

Steven M. Hoffberg  
Milde & Hoffberg, LLP  
Suite 460  
10 Bank Street  
White Plains, NY 10606  
(914) 949-3100 tel.  
(914) 949-3416 fax  
[steve@hoffberg.org](mailto:steve@hoffberg.org)  
[www.hoffberg.org](http://www.hoffberg.org)

Confidentiality Notice: This message, and any attachments thereto, may contain confidential information which is legally privileged. The information is intended only for the use of the intended recipient, generally the individual or entity named above. If you believe you are not the intended recipient, or in the event that this document is received in error, or misdirected, you are requested to immediately inform the sender by reply e-mail at [Steve@Hoffberg.org](mailto:Steve@Hoffberg.org) and destroy all copies of the e-mail file and attachments. You are hereby notified that any disclosure, copying, distribution or use of any information contained in this transmission other than by the intended recipient is strictly prohibited.